

Low Voltage– Fast-Acting Midget

Fast-Acting Supplementary Fuse

- Dimensions:** 13/32" x 1 1/2" (10.3 x 38.1mm)
Volts: 600Vac (or less)
Amps: 1/10-30A
IR: 100kA RMS Sym. (UL)
Agency Information: CE, Std. 248-14, UL Listed, Guide JDYX, File E19180
Typical Applications:
- Control Circuits
 - Lighting Circuit Protection
 - Meter Circuits

Features:

- Low cost supplemental protection of 600V or less non-inductive circuits
- Upgrade with LP-CC product to reduce SKU investment and minimize potential arc-flash hazards



KTK			
Global No.	Description / Case Qty 10	Mars No.	Other
KTK-2	600V 13/32" x 1-1/2" Fast Acting 2A	82911	ATM (Gould)
KTK-3	600V 13/32" x 1-1/2" Fast Acting 3A	82916	CTK (Cefco)
KTK-5	600V 13/32" x 1-1/2" Fast Acting 5A	82913	KLK (Littelfuse)
KTK-10	600V 13/32" x 1-1/2" Fast Acting 10A	82917	MCL (Edison)
KTK-15	600V 13/32" x 1-1/2" Fast Acting 15A	82919	
KTK-20	600V 13/32" x 1-1/2" Fast Acting 20A	82920	
KTK-30	600V 13/32" x 1-1/2" Fast Acting 30A	82922	
KTK-35	600V 13/32" x 1-1/2" Fast Acting 35A	—	