



32" Square Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.

Mustee's 32" square shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. See below...

Features:

- Produced from high grade reinforced molded fiberglass.
- Ideal for new or remodel projects...fits DURABASE® Shower Floors as well as bases from other manufacturers.
- Fits 32" x 32" alcove.
- Includes three (3) large, molded-in, self-draining shelves.
- Three (3) panel wall system with tongue-and-groove seams that assemble quickly to create a watertight wall surround
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- Fits STYLEMATE® Pivot Door with tempered safety glass.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.

Code Accepted:


Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Materials (ASTM) — D 635, E-84 and E-162
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1
- IAPMO® as indicated
- Warnock Hersey® as indicated



Specifications

General: Furnish and install per plans, 32" square, manufactured by E.L. Mustee & Sons, Inc., consisting of:




DURAWALL® SHOWER WALL

Model	Color
732WHT	White
732BN	Bone



DURAWALL® Shower Wall — Model: _____ (732WHT, 732BN) shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Includes center panel and two side panels with three molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color: _____ (White, Bone).




DURABASE® SHOWER FLOOR

Model	Color
3232M	White
3232BN	Bone



DURABASE® Shower Floor — Model: _____ (3232M, 3232BN) floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 32" x 32". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 1/2" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. Color: _____ (White, Bone).



STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
32.705	Chrome/Clear
32.706	Oil-Rubbed Bronze/Clear

STYLEMATE® Pivot-Door — Model _____ (732.705, 732.706) fits 29" to 31" opening. Shall be a Pivot Door with a _____ (chrome, oil-rubbed bronze) finish aluminum frame and clear tempered safety glass panel. Integral-pull handle with magnetic seal. Out-of-plumb conditions up to 1" can be adjusted at latch jamb. Can be installed for right or left opening. Shall meet ANSI Specification Z 97.1.



36" Square Shower Ensembles

DURAWALL® Shower Walls, DURABASE® Shower Floors & STYLEMATE® Enclosures



The dramatic look of a premium-quality shower ensemble from E.L. Mustee & Sons, Inc., is the proven way to transform any bathroom space into something very special.





Mustee's 36" square shower ensembles are created using a DURABASE® shower floor, DURAWALL® shower walls and a STYLEMATE® enclosure. See below...

Features:

- Produced from high grade reinforced molded fiberglass.
- Ideal for new or remodel projects...fits DURABASE® Shower Floors as well as bases from other manufacturers.
- Fits 36" x 36" alcove
- Includes three (3) large, molded-in, self-draining shelves.
- Three (3) panel wall system with tongue-and-groove seams that assemble quickly to create a watertight wall surround
- Mounts direct-to-stud with mounting flanges hidden behind drywall or other wall treatment.
- Fits STYLEMATE® Pivot Door with tempered safety glass.
- All surfaces are mold/mildew resistant, easy to clean, with a deep-gloss finish.


Code Accepted:

Fiberglass Shower Ensembles meet or exceed performance requirements:

- American Society of Testing and Materials (ASTM) — D 635, E-84 and E-162 
- American National Standards Institute (ANSI) — Z 124.1.2 and Z 97.1 
- IAPMO® as indicated 
- Warnock Hersey® as indicated 

Specifications

General: Furnish and install per plans, 36" square, manufactured by E.L. Mustee & Sons, Inc., consisting of:



DURAWALL® SHOWER WALL

Model	Color
736WHT	White
736BN	Bone



DURAWALL® Shower Wall — Model: _____ (736WHT, 736BN) shall be semi-gloss, 3-piece wall. Panels are molded fiberglass, using matched metal molds under extreme heat and pressure with a minimum uniform thickness of 125 mils and mount direct-to-studwalls. Includes center panel and two side panels with three molded-in shelves. Self-aligning panels using a tongue-and-groove connection. Shall meet ANSI Specification Z 124.1.2. Color: _____ (White, Bone).

DURABASE® SHOWER FLOOR

Model	Color
3636M	White
3636BN	Bone




DURABASE® Shower Floor — Model: _____ (3636M, 3636BN) floor to be one-piece, molded fiberglass, made with matched metal molds. Surface to be slip-resistant Starburst® design that does not interfere with the flow of water. Size 36" x 36". Shoulder will be no less than 3" high or less than 1" wide. Tiling flange will extend not less than 1" higher than the threshold which provides an integral molded water barrier. Threshold will be not less than 4 1/2" high. Molded-in drain and drain seal for installation of 2" iron DWV (Sch. 40) PVC or ABS sanitary drain pipe. Removable strainer. Shall meet ANSI Specification Z 124.1.2. Color: _____ (White, Bone).

STYLEMATE® ENCLOSURE

Model	Finish/Type Glass
36.403	Chrome/Clear
36.404	Oil-Rubbed Bronze/Clear

STYLEMATE® Pivot-Door — Model _____ (736.403, 736.406) fits 34" to 35" opening. Shall be a Pivot Door with a _____ (Chrome, Oil-Rubbed Bronze) finish aluminum frame and clear tempered safety glass panel. Integral-pull handle with magnetic seal. Out-of-plumb conditions up to 1" can be adjusted at latch jamb. Can be installed for right or left opening. Shall meet ANSI Specification Z 97.1.



To reorder, specify ADV-494

Notice: Our continuous commitment to product improvement may result in changes to product specifications without notice. Patented and patents pending. ADI/6-12/NM. Made and Printed in U.S.A.