

FITTINGS cont'd

90° Long Radius Bend

90° long radius flat bends are used to route the SpeediChannel™ around an obstacle. The long radius of the elbow allows a gentle bending radius on the copper line set. Each elbow is individually packed, and is furnished complete with stainless steel screws.



230-LFB4

| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|------------------|--------------------------------------|-----|----------------|
| 230-LFB3 | 3" 90 degree Long Radius Bend | EA | 10 |
| 230-LFB3B | 3" 90 degree Long Radius Bend, Brown | EA | 10 |
| 230-LFB4 | 4" 90 degree Long Radius Bend | EA | 10 |
| 230-LFB4B | 4" 90 degree Long Radius Bend, Brown | EA | 10 |
| 230-LFB6 | 6" 90 degree Long Radius Bend | EA | 10 |

90° Inside Elbow

90° inside elbows are used to route the SpeediChannel™ around an inside corner. Each elbow is individually packed, and is furnished complete with stainless steel screws.



230-EB3



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-----------------|----------------------------------|-----|----------------|
| 230-EB3 | 3" 90 degree Inside Elbow | EA | 10 |
| 230-EB3B | 3" 90 degree Inside Elbow, Brown | EA | 10 |
| 230-EB4 | 4" 90 degree Inside Elbow | EA | 10 |
| 230-EB4B | 4" 90 degree Inside Elbow, Brown | EA | 10 |
| 230-EB6 | 6" 90 degree Inside Elbow | EA | 10 |

Union Coupling

Used for joining two pieces of SpeediChannel™ — each cover being the same size. Each coupling is individually packed, and is furnished complete with stainless steel screws.



230-CP3



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-----------------|--------------------------|-----|----------------|
| 230-CP3 | 3" Union Coupling | EA | 10 |
| 230-CP3B | 3" Union Coupling, Brown | EA | 10 |
| 230-CP4 | 4" Union Coupling | EA | 10 |
| 230-CP4B | 4" Union Coupling, Brown | EA | 10 |
| 230-CP6 | 6" Union Coupling | EA | 10 |

45° Flat Bend

45° flat bends are used to route the SpeediChannel™ around an obstacle. Each bend is individually packed, and is furnished complete with stainless steel screws.



230-FB453

| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-------------------|-------------------------------|-----|----------------|
| 230-FB453 | 3" 45 degree Flat Bend | EA | 10 |
| 230-FB453B | 3" 45 degree Flat Bend, Brown | EA | 10 |
| 230-FB454 | 4" 45 degree Flat Bend | EA | 10 |
| 230-FB454B | 4" 45 degree Flat Bend, Brown | EA | 10 |
| 230-FB456 | 6" 45 degree Flat Bend | EA | 10 |

90° Outside Elbow

90° outside elbows are used to route the SpeediChannel™ around an outside corner. Each elbow is individually packed, and is furnished complete with stainless steel screws.



230-EIN3



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|------------------|-----------------------------------|-----|----------------|
| 230-EIN3 | 3" 90 degree Outside Elbow | EA | 10 |
| 230-EIN3B | 3" 90 degree Outside Elbow, Brown | EA | 10 |
| 230-EIN4 | 4" 90 degree Outside Elbow | EA | 10 |
| 230-EIN4B | 4" 90 degree Outside Elbow, Brown | EA | 10 |
| 230-EIN6 | 6" 90 degree Outside Elbow | EA | 10 |

T-Joint

Used for creating a tee connection between three pieces of SpeediChannel™ — all covers being the same size. The tee can be combined with the reducing coupling to join SpeediChannel™s of different sizes. Each tee is individually packed, and is furnished complete with stainless steel screws.



230-TJ4



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-----------------|-------------------|-----|----------------|
| 230-TJ4 | 4" T-Joint | EA | 10 |
| 230-TJ4B | 4" T-Joint, Brown | EA | 10 |
| 230-TJ6 | 6" T-Joint | EA | 10 |