

# 90° Liquidtight Connectors

## Zinc

### Features


- Liquidtight, raintight, oiltight
- 90° connectors
- Assembled with a die cast locknut
- Also available with insulated throat

### Applications

- For use with metallic and non-metallic "Type B" liquidtight conduit

### Standard Material

- Zinc die cast



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches		
						A	B	C
<b>490</b>	14610	<b>3/8" 1/2" KO</b>	10	100	27	2.062	2.34	.52
<b>491</b>	14620	<b>1/2"</b>	10	100	28	2.22	2.34	.52
<b>492</b>	14630	<b>3/4"</b>	10	100	38	2.55	3.55	.68
<b>493</b>	14640	<b>1"</b>	5	50	32	2.82	3.785	.67
<b>494</b>	14650	<b>1-1/4"</b>	2	20	20	3.362	3.96	.70
<b>495</b>	14660	<b>1-1/2"</b>	2	20	26	3.45	4.13	.70
<b>496</b>	14670	<b>2"</b>	1	10	19	4.036	4.70	.57
<b>497</b>	14680	<b>2-1/2"</b>	---	1	4	5.215	5.375	.77
<b>498</b>	14690	<b>3"</b>	---	1	5	6.10	6.50	1.10
<b>499</b>	14700	<b>3-1/2"</b>	---	1	6	6.715	7.45	1.10
<b>500</b>	14710	<b>4"</b>	---	1	7	6.78	8	1.10