

Professional-grade instruments for field service

Model ST4

Dual Temperature Digital Thermometer

ST4 Specifications

Measurement range	-58°F to 400°F (to 2000°F with optional hi-temp thermocouple)
Measurement rate	2.5 readings/second
Resolution	0.1°
Accuracy	±4°F, -58°F to 32°F ±(0.3% rdg + 2°F), -32°F to 1100°F ±(0.5% rdg + 2°F), 1100°F to 2000°F
Accuracy after ice-bucket calibration	±1°F, 30°F to 120°F

Model ST4

Dual Temperature Digital Thermometer



Professional-grade instruments for field service

Model ST4

Dual Temperature Digital Thermometer



ST4: For HVAC/R

Dual Temperature

Take readings of T1, T2, or T1-T2.

Ruggedized

Between the rubber boot and clear-front case there is enough protection for even the most demanding user.

Hands Free Operation

The magnetic hanger and Velcro stabilizing straps give you true hands free operation.

And More:

- LED indicates when a probe is disengaged.
- No adapter to lose.
- "Wrap-tab" for thermocouple storage.
- MIN/MAX and HOLD.



ST4

Clear Case with Magnetic

Velcro Straps

K-type Thermocouples

Rubber Protection



The rubber boot surrounding the ST4 protects the thermometer from regular drops and collisions.

"Wrap-tab" Thermocouple



The wrap-tab on the included thermocouples eliminate all the hassle and wasted time spent untangling thermocouple wires.

Model ST4

Dual Temperature Digital Thermometer

Rugged Thermometer



Velcro Stabilizing Straps



Use the included Velcro straps to stabilize the thermocouple against a pipe.

Connect Any of These Fieldpiece K-type Thermocouples (sold separately)

You can use pipe clamps, wet bulb thermocouples, hi-temp thermocouples or any K-type Fieldpiece thermocouples with the ST4.



Magnetic Hanger

Use the magnetic hanger attached to the back of the case to view the display at desired height.



Professional-grade instruments for field service

Fieldpiece Instruments

Phone: (714) 257-9060 Fax: (714) 257-9069

www.fieldpiece.com