

ACCESSORIES

BUG-LUG™

OXIDE-INHIBITOR ELECTRICAL JOINT COMPOUND

Stable over wide temperature range
 Assures a high-conductivity joint, seals out air and moisture
 Seals out air and moisture from joint to prevent oxidation and corrosion
 Suitable for bolted connector applications and aluminum conduit threads
 Supple round polyethylene squeeze bottle for easy application, wide mouth for wire dipping
 Compact 12-bottle carton (9 inch wide x 6½ inch deep) fits on a small counter or shelf space

BLZNG

Utility Grade

Universal non-petroleum based oxide-inhibitor compound
 Contains homogeneously suspended zinc particles
 Recommended for all AL/AL, AL/CU and CU/CU joints
 Recommended especially for AL/AL and AL/CU compression joints

Metal particles help to break through thin oxide film on aluminum surfaces
 Particles aid in gripping the connector and enhance electrical conductivity
 Compatible with rubber, polyethylene, and most other insulating materials
 Compatible with linesman rubber gloves
 Workable from -10°F to 300°F
 Service Temperature Range -40°F to 350°F
 Will not wash off from exposure to the elements
 Grey color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
13990	BLZNG-8	8 fl. oz. SQUEEZE BOTTLE	12	13	CTN



BLOX

Commercial Grade

Petroleum based oxide-inhibitor compound
 Suitable for all AL/AL, AL/CU, and CU/CU joints
 Suitable for copper joints in direct burial
 Not recommended with rubber gloves or rubber insulating materials
 Compatible with polyethylene and most other insulating materials
 Workable from -20°F to 300°F
 Service Temperature Range -40°F to 300°F
 Amber color

NAED NUMBER	CATALOG NO.	DESCRIPTION	CTN QTY	EST. SHIPPING	
				WEIGHT (lbs)	UNIT
13980	BLOX-8	8 fl. oz. SQUEEZE BOTTLE	12	8	CTN
13982	BLOX-1G	1 Gallon CAN	1	9	EA

