

# Rigid Connectors

## Compression Type - Malleable Iron



### Features

- Compression type connector
- Threadless
- Concrete tight

### Applications

- Dry location only
- Use to join unthreaded Rigid or IMC conduit to steel outlet box or metal enclosure

### Standard Material


- Malleable iron

### Standard Finish

- Zinc plated

### Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>261M</b>	85534	<b>1/2"</b>	20	200	13	1.50	1.50
<b>262M</b>	85535	<b>3/4"</b>	10	100	20	1.50	1.63
<b>263M</b>	85536	<b>1"</b>	5	50	36	1.687	2
<b>264M</b>	85537	<b>1-1/4"</b>	5	50	64	2	2.38
<b>265M</b>	85538	<b>1-1/2"</b>	---	12	92	2.0625	2.63
<b>266M</b>	85539	<b>2"</b>	---	12	117	2.25	3.31
<b>267</b>	12251	<b>2-1/2"</b>	---	5	14	3	3.75
<b>268</b>	12252	<b>3"</b>	---	3	13	3.125	4.25
<b>269</b>	12253	<b>3-1/2"</b>	---	2	13	3.187	4.75
<b>270</b>	12254	<b>4"</b>	---	2	13	3.437	5.312
<b>270A</b>	01493	<b>5"</b>	----	1	7	6.86	4.72
<b>270B</b>	01494	<b>6"</b>	---	1	8	8.14	5.04