

ProPress

Viega ProPress is the trusted copper press joining solution. Since its introduction in 1999, it has reduced overall job costs, saved time and increased reliability on job sites across the globe. Viega is the only company with Smart Connect, an engineered feature that helps installers easily identify an unpressed fitting, providing them with added confidence in their connections. With system-matched tools and jaws, connections are made in less than seven seconds, making Viega ProPress suitable for virtually any type of project.

FEATURES AND BENEFITS

- Available in sizes ½" to 4"
- Customizable with three sealing elements, EPDM, HNBR and FKM
- More than 600 engineered fitting configurations for copper
- Approved for more than 150 different applications

CODES AND STANDARDS

- ABS: American Bureau of Shipping
- CRN: Canadian Registration Number
- CSA International: Canadian Standards Association
- FM: FM Global
- IAPMO: Uniform Plumbing Code
- ICC: International Plumbing Code
- NFPA 13, 13D and 13R: Fire Sprinkler Applications
- NSF/ ANSI 61: Drinking Water System Components Health Effects
- NSF/ ANSI 372: Drinking Water System Components Lead Content
- PHCC: National Standard Plumbing Code
- UL: Underwriters Laboratories

LISTINGS AND CERTIFICATIONS

- CRN 0A14541.5 A/B/C
- CSA MSE-13
- FM Class 1920
- IAPMO PS117
- ICC-ES PMG-1037
- NSF 61
- NSF 372
- ULC/ORD 213

ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).

NOTE

A Green Dot on a Viega ProPress fitting indicates the Smart Connect feature with an EPDM sealing element.

Adapters


**Viega ProPress adapter
Smart Connect feature, Zero Lead**

- For use with ASTM B88 tubing
- Bronze
- Press connection, male pipe thread

Components

EPDM sealing element

Model 2911ZL

P	MPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.090	10	79210	8
1/2	1/2	0.105	10	79215	8
1/2	3/4	0.149	10	79220	8
3/4	1/2	0.147	10	79225	8
3/4	3/4	0.159	10	79230	8
3/4	1	0.238	10	79235	8
1	3/4	0.229	10	79240	8
1	1	0.259	10	79245	8
1	1 1/4	0.450	10	79250	8
1 1/4	1	0.317	1	79255	8
1 1/4	1 1/4	0.441	1	79260	8
1 1/4	1 1/2	0.521	1	79265	8
1 1/2	1 1/4	0.599	1	79270	8
1 1/2	1 1/2	0.538	1	79275	8
1 1/2	2	0.934	1	79280	8
2	1 1/2	0.842	1	79285	8
2	2	0.906	1	79290	8


**Viega ProPress adapter
Zero Lead**

- For use with Viega ProPress fittings
- Bronze
- Street, male pipe thread

Model 2911.1ZL

FTG	MPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.069	5	79375	8
1/2	1/2	0.103	5	79380	8
1/2	3/4	0.137	5	79385	8
3/4	1/2	0.102	5	79390	8
3/4	3/4	0.148	5	79395	8
1	3/4	0.177	5	79400	8
1	1	0.245	5	79405	8
1 1/4	1 1/4	0.499	1	79410	8
1 1/2	1 1/2	0.560	1	79415	8
2	2	0.910	1	79420	8


**Viega ProPress XL-C adapter
Smart Connect feature**

- For use with ASTM B88 tubing
- Copper
- Press connection, male pipe thread

Components

EPDM sealing element

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0911XL

P	MPT	Wt [lb]	Quantity	Part No	DG
2 1/2	2 1/2	1.585	1	20823	8
3	3	2.314	1	20828	8
4	4	3.643	1	20838	8


**Viega ProPress adapter
Smart Connect feature, Zero Lead**

- For use with ASTM B88 tubing
- Bronze
- Press connection, female pipe thread

Components

EPDM sealing element

Model 2912ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	3/8	0.083	10	79295	8
1/2	1/2	0.120	10	79300	8
1/2	3/4	0.151	10	79305	8
3/4	1/2	0.145	10	79310	8
3/4	3/4	0.174	10	79315	8
1	1/2	0.181	10	79320	8
1	3/4	0.206	10	79325	8
1	1	0.277	10	79330	8
1	1 1/4	0.366	10	79335	8
1 1/4	1/2	0.220	1	79340	8
1 1/4	1	0.308	1	79345	8
1 1/4	1 1/4	0.388	1	79350	8
1 1/4	1 1/2	0.463	1	79355	8
1 1/2	1 1/4	0.331	1	79360	8
1 1/2	1 1/2	0.546	1	79365	8
2	2	0.765	1	79370	8