

Heavy Duty Floats

Copper Floats



High grade copper construction.
Firmly bonded overlapping joints (leadfree solder).

Maximum Temperature - 200°F

| Diameter Size | Model | Thread Connection | Inner Pack | Master Pack | Weight each (oz.) |
|---------------|-------|-------------------|------------|-------------|-------------------|
| 4" x 5" | CX | ¼-20 | 1 | 8 | 2.6 |
| 4" | C4 | ¼-20 | 1 | 8 | 4.3 |
| 5" | C5 | ¼-20 | 1 | 12 | 6.5 |
| 6" | C6 | ¼-20 | 1 | 8 | 8.3 |
| 6" | C6-7 | 5/16-18 | 1 | 8 | 8.3 |
| 6" | C6-3 | 3/8-16 | 1 | 24 | 8.3 |
| 7" | C7 | 5/16-18 | 1 | 12 | 15.3 |
| 8" | C8 | 3/8-16 | 1 | 8 | 20.0 |
| 10" | C10 | 3/8-16 | 1 | 4 | 44.0 |
| 12" | C12 | 3/8-16 | 1 | 4 | 67.0 |

Plastic Floats



Non-electrolytic, highly corrosion resistant. Unaffected by salts and caustic fluids. All injection molded Polyethylene construction. Resistant to sunlight deterioration.

Maximum Temperature - 140°F

| Diameter Size | Model | Inner Pack | Master Pack | Weight each (oz.) |
|---------------|-------|------------|-------------|-------------------|
| 4" x 5" | PX | 1 | 10 | 2.3 |
| 6" | P6 | 1 | 10 | 7.3 |
| 6" | P6-7 | 1 | 10 | 7.3 |
| 8" | P8 | 1 | 10 | 12.6 |
| 8" | P8-7 | 1 | 10 | 12.6 |
| 8" | P8-1 | 1 | 10 | 12.6 |
| 2 pcs. 6" | P12 | 1 | 1 | 14.6 |
| 2 pcs. 8" | P16 | 1 | 1 | 25.1 |

* Assembly of two P6's.

** Assembly of two P8's.

Heavy Duty Float Valve Replacement Parts




1MN
(Long Arm)

2MN
(Short Arm)

Valve Arms (Bronze)

For valve sizes 3/8", 1/2" and 3/4"

| Model | Thread Size | Inner Pack | Master Pack |
|-------|-------------|------------|-------------|
| 1MN | N/A | 10 | 100 |
| 2MN-1 | ¼-20 | 10 | 100 |
| 2MN-7 | 5/16-18 | 10 | 100 |
| 2MN-3 | 3/8-16 | 10 | 100 |
| 2MN-9 | 1/8 | 10 | 100 |



1JB
(Long Arm)

2JB
(Short Arm)

Valve Arms (Bronze)

For valve sizes 1" through 2"

| Model | Thread Size | Inner Pack | Master Pack |
|-------|-------------|------------|-------------|
| 1JB | N/A | 10 | 100 |
| 2JB-1 | ¼-20 | 10 | 100 |
| 2JB-7 | 5/16-18 | 10 | 100 |
| 2JB-3 | 3/8-16 | 10 | 100 |
| 2JB-9 | 1/8 NPSF | 10 | 100 |
| 2JB-4 | ¼ NPSF | 10 | 100 |