

# LEAK DETECTION

# PROWLER

<b>WARRANTY</b> 24 MONTHS	<b>SENSOR LIFE</b> UP TO 10 YEARS	<b>ALARM</b> AUDIBLE, VISUAL BAR GRAPHS, AND SILENT VIBRATING HANDLE	<b>NEW</b> MANUAL RESET
------------------------------	--------------------------------------	--	----------------------------

## LD-5000 REFRIGERANT LEAK DETECTOR



The Prowler features manual calibration mode and reset control. It's highly sensitive electrochemical sensor detects all HFC, HCFC, and HFO refrigerants, helping you find even the smallest of leaks.

### FEATURES

- Certified to ASHRAE standard 173-2012
- Sensitivity can be programmed to high, medium, low
- Proprietary electrochemical sensor does not diminish over time or with use
- Warm up time < 30 seconds; response time immediate
- Mutable audio alarm backed up by silent vibrating handle alarm
- Adjustable back-lit LCD screen tilts upward for easy viewing at any angle
- 17" Flexible probe
- Leak indicator bar graph displays leak intensity
- Low battery consumption and excellent circuit stability
- Four AA alkaline batteries (included)
- Extremely accurate for all HFC, HCFC and blended refrigerants as well as new HFO refrigerants



<b>R410A</b> .05 oz/yr	<b>R22</b> .025 oz/yr
<b>R404A</b> .05 oz/yr	<b>R134a</b> .05 oz/yr
<b>R407A</b> .05 oz/yr	<b>R427A</b> .05 oz/yr
<b>R1234yf</b> .0125 oz/yr	

*R1234yf is a low GWP alternative HFO refrigerant for HFC and HCFC refrigerants that are currently being phased out by the U.S. EPA. It is an A2L flammable refrigerant as defined by ASHRAE 34.*

### CERTIFICATIONS

CE, ASHRAE 173-2012, EN 14624: 2012, SAE J2791, and SAE J2913

LD-5000	
PART NO.	DESCRIPTION
LD-5000	Prowler leak detector in case
LD-S100	Replacement sensor (3 prong)
LD-S101	Replacement sensor (6 prong)
LD-RF5	Replacement filters (5 pack)
LD-TV	Replacement leak test vial
LD-PK	Parts kit (6-prong sensor, filter kit and test vial)
LD-CS	Carrying case