

## Scotch® Linerless Rubber Splicing Tape 130C

Scotch® Linerless Rubber Splicing Tape 130C is a highly conformable, linerless Ethylene Propylene Rubber (EPR), high-voltage insulating tape that provides excellent thermal dissipation of splice heat. Scotch® Splicing Tape 130C meets industry specifications and has excellent physical and electrical properties, which help provide immediate moisture seal and void-free buildups. Scotch® Splicing Tape 130C is rated up to 194°F (90°C) continuous operating temperatures and short-term 266°F (130°C) overload service. This product can be used for low and high-voltage (through 69 kV) applications. This tape should be applied like any rubber tape—that is, the side of the tape wrapped inside the roll should be applied outside on the splice (tacky side up). This will help prevent the roll from getting progressively further away from the work area.

<b>Liner/Linerless</b>	Linerless
<b>Material</b>	Self-fusing Ethylene Propylene Rubber (EPR)
<b>Tape Grade</b>	Premium
<b>Tape Type</b>	Insulating and Splicing
<b>Operating Temperature</b>	Up to 194°F (90°C)
<b>Short Term Overload Service</b>	266°F (130°C)
<b>RoHS 2011/65/EU</b>	Yes
<b>Specifications</b>	ASTM D-4388 type 1, 2 & 3; HH-I-553C
<b>Country of Origin</b>	



Order No.	UPC	Color	Length	Width	Thickness	Elongation	Breaking Strength	Rolls per Carton	Rolls per Case
130C-3/4X30FT	054007-41717	Black	30'	0.75"	30 mil	850%	7.5 lbs/in	1	24
130C-1X10FT	054007-41751	Black	10'	1.00"	30 mil	850%	7.5 lbs/in	1	24
130C-1X15FT	054007-41752	Black	15'	1.00"	30 mil	850%	7.5 lbs/in	1	24
130C-1X30FT	054007-41753	Black	30'	1.00"	30 mil	850%	7.5 lbs/in	1	24
130C-1-1/2X30FT	054007-41718	Black	30'	1.50"	30 mil	850%	7.5 lbs/in	1	12
130C-2X30FT	054007-41754	Black	30'	2.00"	30 mil	850%	7.5 lbs/in	1	12