


# DIMENSIONAL SPECIFICATIONS

## LEAD-FREE IMPORT BRASS FITTINGS\* 125 LB.

### HEX BUSHING CONTINUED

Part #	Size (IN.)	Approx. Net WT. (LB.)	A	B	C
XNL114-2408	1-1/2 X 1/2	0.72	0.83	0.43	0.37
XNL114-2412	1-1/2 X 3/4	0.50	0.83	0.50	0.37
XNL114-2416	1-1/2 X 1	0.49	0.83	0.58	0.31
XNL114-2420	1-1/2 X 1-1/4	0.43	0.83	0.71	0.31
XNL114-3208	2 X 1/2	1.10	0.88	0.43	0.43
XNL114-3212	2 X 3/4	1.15	0.88	0.50	0.43
XNL114-3216	2 X 1	1.02	0.88	0.58	0.41
XNL114-3220	2 X 1-1/4	0.87	0.88	0.67	0.34
XNL114-3224	2 X 1-1/2	0.81	0.88	0.70	0.34
XNL114-4016	2-1/2 X 1	1.76	1.09	0.59	0.44
XNL114-4020	2-1/2 X 1-1/4	1.67	1.09	0.69	0.44
XNL114-4024	2-1/2 X 1-1/2	1.15	1.09	0.72	0.44
XNL114-4032	2-1/2 X 2	5.98	1.07	0.75	0.37
XNL114-4824	3 X 1-1/2	2.44	1.13	0.72	0.50
XNL114-4832	3 X 2	1.70	1.13	0.75	0.48
XNL114-4840	3 X 2-1/2	1.69	1.13	0.92	0.40
XNL114-6432	4 X 2	3.16	1.22	0.75	0.60
XNL114-6448	4 X 3	3.74	1.22	0.98	0.50



\*Conforms with lead content requirements for lead-free plumbing as defined by the U.S. Safe Drinking Water Act. Certified <0.25 weighted average % lead.



# MERIT BRASS

DIRECTING THE FLOW OF *Quality*