



[Pads & Bulk Media]

- Progressively Dense Fiberglass or 100% Non-woven Polyester
- Standard and Special Sizes Available
- Skin Backing on Air Leaving Side of Fiberglass
- Service Roll in Easy-to-Use Cardboard Dispenser Box

FEATURES



Glasfloss offers a variety of pre-cut pads and bulk media for pre-filter or primary filter applications. Glasfloss pre-cut pads and bulk media come in a variety of fiberglass and 100% non-woven polyester grades that are designed for light to heavy dust-loading applications. Standard size pre-cut pads are packaged in a heavy-duty carton that allows quick access and keeps the media clean before installation. Service rolls are available and are packaged in an easy to use cardboard dispenser box.



SPECIFICATIONS

Media Type	Color	Nominal Thickness	Media Structure	Adhesive	Backing
Commercial	White	1" & 2"	Progressive Density Fiberglass	Light	"Skin"
Paint Arrestor	Green/White	2-1/2"	Progressive Density Fiberglass	-	"Skin"
HI-PAK®	Yellow/White	3"	Progressive Density Fiberglass	Heavy	"Skin"
HL-4	White	1"	Non-Woven Polyester	-	-
HL-8	White	2"		-	-
125-4P	Blue/White	5/8"	Non-Woven Polyester	Moderate	-
125-7P	Blue/White	1"		Moderate	-
P5T	Green/White	1/2"	Multi-ply Polyester	Moderate	-
P10T	Orange/White	1"	Multi-ply Polyester	Moderate	-
P20T	Orange/White	2"	Multi-ply Polyester	Moderate	-
Hoghair	Blue	1"	Synthetic Fibers	-	-


Pads and Bulk Media Specifications

COMMERCIAL	PAINT ARRESTOR	HI-PAK
<ul style="list-style-type: none"> · Continuous Filament Fiberglass · 1" & 2" Nominal Thicknesses Available · Graduated Density · Skin Backing · Moderate Dust Loading Capacity · 74%-79% Average Arrestance Efficiency · White Color · U.L. Classified 	<ul style="list-style-type: none"> · Continuous Filament Fiberglass · 2-1/2" Nominal Thickness · Graduated Density · Skin Backing · High Paint Holding Capacity · 99.3% Average Removal Efficiency · Green on Air Entering Side · U.L. Classified 	<ul style="list-style-type: none"> · Continuous Filament Fiberglass · 3" Nominal Thickness · Graduated Density · Skin Backing · High Dust Holding Capacity · Yellow on Air Entering Side · Non-flammable, Non-toxic Odor Free Adhesive · 85% Average Arrestance Efficiency · U.L. Classified

HL-4	HL-8	HOGHAIR
<ul style="list-style-type: none"> · 100% Non-woven Polyester · 1" Nominal Thickness · Moderate Dust Holding Capacity · Fire Retarding Bonding Agent · 82% Average Arrestance Efficiency · White Color · U.L. Classified 	<ul style="list-style-type: none"> · 100% Non-woven Polyester · 2" Nominal Thickness · Moderate Dust Holding Capacity · Fire Retarding Bonding Agent · 83% Average Arrestance Efficiency · White Color · U.L. Classified 	<ul style="list-style-type: none"> · 100% Synthetic Fibers · 1" Nominal Thickness · Interlocking Fiber Design · Heavy Dust Holding Capacity · Cleanable by Vacuuming, Tap Water Rinsing, Hosing or Immersion in a Detergent Solution · Blue Color · U.L. Classified


STANDARD PRESSURE DROP

Test Filter Size 24" x 24" Nominal



STANDARD PRESSURE DROP

Test Filter Size 24" x 24" Nominal



Pads and Bulk Media Specifications

125-4P

- 100% Non-woven Polyester
- 5/8" Nominal Thickness
- Graduated Density
- Non-toxic, Non-migratory Adhesive Second Stage
- Light Dust Holding Capacity
- 84% Average Arrestance Efficiency
- White on Air Entering Side
- U.L. Classified

125-7P

- 100% Non-woven Polyester
- 1" Nominal Thickness
- Graduated Density
- Non-toxic, Non-migratory Adhesive Second Stage
- Moderate Dust Holding Capacity
- 86% Average Arrestance Efficiency
- White on Air Entering Side
- U.L. Classified

P5T

- 100% Non-woven Polyester
- 1/2" Nominal Thickness
- Fire Retarding Bonding Agent
- Dual Denier Fiber Configuration
- Non-toxic, Non-migratory Adhesive Second Stage
- Moderate Dust Holding Capacity
- 82% Average Arrestance Efficiency
- White on Air Entering Side
- U.L. Classified

P10T


- 100% Non-woven Polyester
- 1" Nominal Thickness
- Fire Retarding Bonding Agent
- Dual Denier Fiber Configuration
- Dual Layer Filtration Stages
- Non-toxic, Non-migratory Adhesive Second Stage
- Heavy Dust Holding Capacity
- 92% Average Arrestance Efficiency
- White on Air Entering Side
- U.L. Classified
- MERV 8

P20T

- 100% Non-woven Polyester
- 2" Nominal Thickness
- Fire Retarding Bonding Agent
- Dual Denier Fiber Configuration
- Dual Layer Filtration Stages
- Non-toxic, Non-migratory Adhesive Second Stage
- Heavy Dust Holding Capacity
- 93% Average Arrestance Efficiency
- White on Air Entering Side
- U.L. Classified
- MERV 8


STANDARD PRESSURE DROP

Test Filter Size 24" x 24" Nominal



MINIMUM PARTICLE SIZE EFFICIENCY

Test Filter Size 24" x 24" Nominal



"Serving You With Locations Throughout The Nation"

Glasfloss has a policy of uninterrupted research, development and product improvement and reserves the right to change design and specifications without notice.

www.glasfloss.com · (214) 741-7056

> **CONSTRUCTION SPECIFICATIONS FOR PADS AND BULK MEDIA**

Fiberglass: Shall consist of continuous filament fiberglass of graduated density to ensure depth loading and long service life. The air-exit side of the fiberglass media shall incorporate a skin backing which supports the media during operation and creates a final filtration stage. The various grades of fiberglass media are engineered for a variety of dust-loading applications and shall be treated with a non-toxic, non-flammable, odorless adhesive. The paint arrestor media is engineered for various paint over-spray applications and does not contain adhesive.

Polyester: Shall consist of 100% non-woven polyester fibers bonded together. The polyester pre-cut pads and bulk media are engineered for a variety of applications and available in single or multi-ply grades. The polyester pre-cut pads and bulk media are available dry or treated with a non-toxic, non-migratory, odorless adhesive that is incorporated into the filter media.



Glasfloss is proud to be an Energy Star Partner. The Energy Star Service and Product Provider Partnership is available to organizations that provide energy efficiency related products and/or services to the commercial buildings and industrial plants in the United States.



Glasfloss manufactures a variety of medium and high efficiency air filters which can be specified for LEED certification applications. For specific information on these products, please contact your local Glasfloss Sales Representative.

