



VCCA-20ULS SERIES

APPLICATIONS

- Designed for automatic collection and removal of condensate from air conditioning, refrigeration, and dehumidification equipment when gravity drainage is not possible or practical. The VCCA Series' low tank height allows these condensate pumps to be used where other condensate pumps will not fit.
- Suitable for high efficiency condensing furnace and boiler equipment applications.



FEATURES

- 1/30 hp motor
- Low profile for limited space applications
- 1/4-turn, twist-off locking check valve discharge adapter for 3/8" ID tubing
- Additional check valve adapter included for 1/4" ID vinyl tubing
- Pump switch test lever (for manual test operation)
- Rubber feet on bottom of tank to isolate pump when placed on hard surface
- 3 inlet openings suitable for 3/4" PVC pipe
- Easy-to-knock-out plugs in two of the inlet openings
- Includes overflow detection switch with 5" leads
- ABS tank, motor cover, and volute
- Intermittent liquid temperature up to 120 °F
- Stainless steel motor shaft
- Thermal overload protection
- cCSAus


SERIES SPECIFICATIONS


Item No.	Model	НР	Volts	Hz	Amno	Watts	Watts Discharge		Gallons per hour (Liters per hour) @ Height				PSI	Cord	Weight
item No.	Piodei	пР	VOILS	П	Amps	Walls	Discharge	l'	5'	10'	18'	Shut-Off	P31	Colu	lbs (kg)
554201101	VCCA-20ULS	1/30	115	60	1.5	93	3/8" (9.5mm) OD Barded	80 (303)	70 (265)	45 (171)	10 (38)	20' (6.1m)	8.6	6' (1.8m)	5.4 (2.5 kg)
554202101	VCCA-20ULS	1/30	230	50/60	0.6/0.5	75	3/8" (9.5mm) OD Barded	80 (303)	70 (265)	45 (171)	10 (38)	17' (5.2m)	7.4	6' (1.8m)	5.4 (2.5 kg)

Note: Flow rating is through check valve

VCCA-20ULS SERIES


ENGINEERING DATA





А	В	С	D	Е	F	G	Н			К	L	М
11.96"	2.02"	1.70"	1.18"	2.52"	3.85"	8.55"	5.02"	5.23"	1.85"	1.52"	0.27"	11.42"
(303.7 mm)	(51.4 mm)	(43.2 mm)	(30 mm)	(64 mm)	(98 mm)	(217.4 mm)	(127.6 mm)	(133 mm)	(47 mm)	(38.8 mm)	(6.9 mm)	(290 mm)

PERFORMANCE DATA



CONSTRUCTION

Motor	1/30 hp
Discharge	3/8" O.D. barbed
Housing/Tank Cover	ABS
Motor Cover	ABS
Volute	ABS
Tank	ABS
Impeller	Polypropylene
Check Valve	Acetal