

INTEGRAL BRACKET SLIM LINE®

- Point-of-Use filter housings
- Available with 3/8-inch NPT or quick connect inlet/outlet
- Integral mounting bracket
- Pressure relief button



Tested and Certified by NSF International.

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
W38-PRB	152086	Gray	Black	3/8" NPT	5-1/4" x 13-1/2"	30 - 125 psi	40 - 100° F	WW38
W38-PRQC	152085	Gray	Black	3/8" QC	5-1/4" x 13-1/2"	30 - 125 psi	40 - 100° F	WW38



W38-PRB

W38-PRQC

INTEGRAL BRACKET STANDARD

- Whole-house filter housings
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Integral mounting bracket
- Clear or opaque sump
- Accepts a wide variety of 2-1/2 to 3-inch diameter cartridges

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
W34-PRB	152084	Gray	Black	3/4" NPT	5-3/4" x 12-1/4"	30 - 125 psi	40 - 100° F	WW34
WC34-PRB*	152083	Clear	Black	3/4" NPT	5-3/4" x 12-1/4"	30 - 125 psi	40 - 100° F	WW34

*Not Performance Tested or Certified by NSF.



WC34-PRB

W34-PRB

MONITORED WHOLE HOUSE

- Whole-house filter housing
- Three-color monitor indicates when to change the filter
- 3/4-inch NPT inlet/outlet
- Pressure relief button
- Integral mounting bracket
- Includes WPD-110, 5-micron sediment cartridge
- Includes WW34 housing wrench
- Accepts a wide variety of 2-1/2 to 3-inch diameter cartridges

MODEL NUMBER	PART NUMBER	SUMP COLOR	CAP COLOR	INLET/OUTLET	OVERALL DIMENSIONS	OPERATING PRESSURE	OPERATING TEMPERATURE	OPTIONAL ACCESSORIES†
W34-PRM	152082	Gray	Black	3/4" NPT	5-3/4" x 15"	30 - 125 psi	40 - 100° F	WMB34, WW34



W34-PRM

†See page 14 for part number and description. Note: See chart on page 16 for flow rates with specific cartridges.