



# Residential/Commercial Vacuum Pumps

## HUMM-VAC®

**FOR U.S. JOBS**  
UNIWELD EMPLOYS OVER 300 WORKERS

The Uniweld exclusive HUMM-VAC® Pumps remove moisture and dehydrate a system quickly and efficiently. The all-metal, heavy duty chassis; powerful, quiet running dual voltage motor; lighter weight and ergonomically designed features make these pumps the #1 choice to go to work with you.



### Pump Specifications

### HVP6

### HVP8

### HVP12

	HVP6	HVP8	HVP12
Free Air Displacement	6.0 CFM, 170 liter/min	8.0 CFM, 226 liter/min.	12.0 CFM 340 liter/min.
Number of Stages	2-Stage Rotary Vane	2-Stage Rotary Vane	2-Stage Rotary Vane
Factory Micron Rating	15 Microns	15 Microns	15 Microns
3-Way Intake Fittings	1/4" & 3/8" Male Flare; 1/2" Acme	1/4", 3/8" & 1/2" Male Flare	1/4", 3/8" & 1/2" Male Flare
Thermal Overload Protection	1/2 HP	3/4 HP	3/4 HP
Voltage	110/220V - 50/60Hz	110/220V - 50/60Hz	110/220V - 50/60Hz
Oil Capacity	1 Quart [946ml]	31.3 Ounces [925 ml]	27.7 Ounces [820 ml]
Power Cord*	72" [1.83m], U.S. -Type B Plug	72" [1.83m], U.S. -Type B Plug	72" [1.83m], U.S. -Type B Plug
Dimensions	14.50" x 6.875" x 10.75" 36.83 cm x 17.46 cm x 27.30 cm	15.0" x 6.875" x 10.75" 38.1 cm x 17.46 cm x 27.3 cm	15.0" x 6.875" x 10.75" 38.1 cm x 17.46 cm x 27.3 cm
Weight	26 lbs. [11.80 kg]	34 lbs. [15.42 kg]	35 lbs. [15.88 kg]
Shipping Weight	30 lbs. [13.60 kg]	38 lbs. [17.24 kg]	39 lbs. [17.70 kg]
Color	Yellow	Red	Black

5 HVAC/R TOOLS

HUMM-VAC® Pumps

\*Optional Int'l Power Cord Available on request

