

CARBON IMPREGNATED CELLULOSE



- Point-of-Use filter cartridges
- Economically priced
- Dual-purpose cartridges
- Design maximizes dirt-holding capacity
- Reduce bad taste and odor, chlorine taste & odor, and sediment (as tested by American Plumber)
- Designed for municipal/chlorinated water (not recommended for well water)



The W5CIP is Tested and Certified by NSF International, for material requirements only!

MODEL NUMBER	PART NUMBER	MEDIUM	CHLORINE T & O REDUCTION @ FLOW RATE	MAXIMUM FLOW RATE	DIAMETER	LENGTH
W5CIP478	155022-52	Carbon-impregnated Cellulose	>2,500 gal @ 0.5 gpm*	2 gpm	2-1/2"	4-7/8"
W5CIP	155002-52	Carbon-impregnated Cellulose	>5,000 gal @ 1 gpm*	5 gpm	2-5/8"	9-3/4"


GRANULAR ACTIVATED CARBON



- Point-of-Use filter cartridges
- Effective taste, odor, and chlorine taste & odor reduction
- Nominal 20-micron postfilter reduces suspended particles by mechanical means
- Cartridge design ensures that water passes through the entire length of the carbon bed, maximizing contact time

MODEL NUMBER	PART NUMBER	MEDIUM	CHLORINE T & O REDUCTION @ FLOW RATE	MAXIMUM FLOW RATE	DIAMETER	LENGTH
WGC478	155110-51	Granular-Activated Carbon	>750 gal @ 0.5 gpm*	1 gpm	2-7/8"	4-7/8"
WCC	155155-51	Granular-Activated Coconut Carbon	>500 gal @ 1 gpm*	1 gpm	2-7/8"	9-3/4"
WGCHD	155153-51	Granular-Activated Carbon	>12,500 gal @ 2 gpm*	2 gpm	4-1/2"	9-3/4"

CARBON BLOCK



- Point-of-Use filter cartridges
- Excellent bad taste, odor, and chlorine taste & odor reduction (as tested by American Plumber)
- Available in a wide range of sizes to fit both Standard and Heavy duty filter housings
- Specialty blocks are capable of reducing cysts*, lead and certain volatile organic chemicals (VOCs) (as tested by American Plumber)



Tested and Certified by NSF International, for material requirements only!

MODEL NUMBER	PART NUMBER	MEDIUM	REDUCES	RATING (NOMINAL)	CHLORINE T & O REDUCTION @ FLOW RATE	LEAD	VOCs	DIA.	LENGTH
W5CB478	155169-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>3,000 gal @ 1 gpm**	N/A	N/A	2-7/8"	4-7/8"
W5CB	155162-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>20,000 gal @ 1 gpm**	N/A	N/A	2-7/8"	9-3/4"
W5CBHD	155170-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>5,000 gal @ 4 gpm**	N/A	N/A	4-5/8"	9-3/4"
WLC-R	155268-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*, Lead, VOCs*	0.5 micron	>20,000 gal @ 0.6 gpm**	600*	300*	2-7/8"	9-3/4"

*NSF/ANSI Standard 53 certified to reduce cysts such as *Cryptosporidium* and *Giardia* by mechanical means.

**As tested by American Plumber. Certain states require registration for health-related claims.