



Air

Package Heat Pump  
RQPL Series

The new degree of comfort.™



## Rheem *Commercial Classic*® Series Package Heat Pump



**RQPL- High Efficiency 14-SEER Series**  
Nominal Sizes 2-4 Tons [7.03-14.07 kW]



INTEGRATED AIR & WATER

**208-240 VOLT, SINGLE PHASE, 60 HZ, AUXILIARY ELECTRIC HEATER KITS CHARACTERISTICS AND APPLICATION**

Single Power Supply For Both Unit and Heater Kit										Separate Power Supply For Both Unit and Heater Kit							
Unit Model No. RQPL-	Heater Kit					Heat Pump					Heater Kit			Heat Pump			
	RXQJ-Heater Kit Nominal kW	No. of Elements	No. of Sequence Steps	Rated Heater kW @ 208-240 V	Heater KBTU/Hr @ 208-240 V	Heater Amp. @ 208-240 V	Unit Min. Ckt. Ampacity @ 208-240 V	Over Current Protective Device Size @ 240 V		Min. Circuit Ampacity 208-240 V	Max. Fuse Size 208/240V	Min. Ckt. Ampacity 208/240V	Over Current Protective Device Size @ 208 V		Min. Circuit Ampacity 208-240 V	Max. Fuse Size 208/240V	Min. Ckt. Ampacity 208/240V
								Min./Max.	Min./Max.				Min./Max.	Min./Max.			
B024JK	No Heat	—	—	—	—	—	21/21	30/30	30/30	21/21	—	—	30/30	30/30	—	—	—
B025JK	A05J A10J	1 2	1 2	3.6/4.8 7.2/9.6	12.28/16.38 24.56/32.75	17.3/20.0 34.6/40.0	42/46 64/71	50/50 70/80	50/50 70/80	—	25/25 45/50	—	—	—	—	—	—
B030JK	No Heat	—	—	—	—	—	24/24	35/35	35/35	24/24	—	—	35/35	35/35	—	—	—
B030JK	A05J A10J	1 2	1 2	3.6/4.8 7.2/9.6	12.28/16.38 24.56/32.75	17.3/20.0 34.6/40.0	45/49 67/74	50/50 70/80	50/50 70/80	—	25/25 45/50	—	—	—	—	—	—
B036JK	No Heat	—	—	—	—	—	27/27	40/40	40/40	27/27	—	—	40/40	40/40	—	—	—
B036JK	A10J A15J	2 3	2 2	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	34.6/40.0 51.9/60.0	70/77 92/102	70/80 100/110	70/80 100/110	—	45/50 70/80	—	—	—	—	—	—
B042JK	No Heat	—	—	—	—	—	33/33	50/50	50/50	33/33	—	—	50/50	50/50	—	—	—
B042JK	B10J B15J	2 3	2 2	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	34.6/40.0 51.9/60.0	77/83 98/108	80/90 100/110	80/90 100/110	—	45/50 70/80	—	—	—	—	—	—
B048JK	No Heat	—	—	—	—	—	37/37	50/50	50/50	37/37	—	—	50/50	50/50	—	—	—
B048JK	B10J B15J	2 3	2 2	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	34.6/40.0 51.9/60.0	80/87 102/112	90/90 110/125	90/90 110/125	—	45/50 70/80	—	—	—	—	—	—

**208-240 VOLT, THREE PHASE, 60 HZ, AUXILIARY ELECTRIC HEATER KITS CHARACTERISTICS AND APPLICATION**

Single Power Supply For Both Unit and Heater Kit										Separate Power Supply For Both Unit and Heater Kit							
Unit Model No. RQPL-	Heater Kit					Heat Pump					Heater Kit			Heat Pump			
	RXQJ-Heater Kit Nominal kW	No. of Elements	No. of Sequence Steps	Rated Heater kW @ 208-240 V	Heater KBTU/Hr @ 208-240 V	Heater Amp. @ 208-240 V	Unit Min. Ckt. Ampacity @ 208-240 V	Over Current Protective Device Size @ 240 V		Min. Circuit Ampacity 208-240 V	Max. Fuse Size 208/240V	Min. Ckt. Ampacity 208/240V	Over Current Protective Device Size @ 208 V		Min. Circuit Ampacity 208-240 V	Max. Fuse Size 208/240V	Min. Ckt. Ampacity 208/240V
								Min./Max.	Min./Max.				Min./Max.	Min./Max.			
B036CK	No Heat	—	—	—	—	—	19/19	25/25	25/25	19/19	—	—	25/25	25/25	—	—	—
B036CK	A10C A15C	3 3	3 3	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	20.0/23.1 30.1/34.7	44/48 57/62	45/50 60/70	45/50 60/70	—	25/30 40/45	—	—	—	—	—	—
B042CK	No Heat	—	—	—	—	—	25/25	35/35	35/35	25/25	—	—	35/35	35/35	—	—	—
B042CK	A10C A15C	3 3	3 3	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	20.0/23.1 30.1/34.7	50/54 63/68	50/60 70/70	50/60 70/70	—	25/30 40/45	—	—	—	—	—	—
B048CK	No Heat	—	—	—	—	—	26/26	35/35	35/35	26/26	—	—	35/35	35/35	—	—	—
B048CK	A10C A15C	3 3	3 3	7.2/9.6 10.8/14.4	24.56/32.75 36.84/49.13	20.0/23.1 30.1/34.7	51/55 63/69	60/60 70/70	60/60 70/70	—	25/30 40/45	—	—	—	—	—	—